Product information

PI 55/08/01/2025

Pro-Line Gasoline System Cleaner



Description

Removes deposits on injectors, intake valves, spark plugs and in the combustion chamber and prevents new deposits from forming. Eliminates starting problems and rough engine running. Cares for all components of the gasoline injection system and protects the entire fuel system against corrosion. Improves the throttle response and compression. Optimizes the emission test values and the performance of the engine. Clean engines consume less fuel and emit fewer pollutants.

Properties

- increases operational reliability
- reduces pollutant emissions
- cleans the fuel system
- assures an optimum mixture
- guarantees low fuel consumption
- simple to use
- removes deposits on injectors and in the combustion chamber
- outstanding corrosion protection

Technical data

Base	additive mixture in liquid carrier
Color / appearance	yellowish, light orange
Regulation on Flammable Liquids Class (Germany)	A III
Flash point	> 61 °C
Pour point	< -60 °C
Form	liquid
Odor	aromatic
Viscosity at 40 °C	<7 mm²/s
Density at 15 °C	0,81 g/ml

Areas of application

For all gasoline engines, gasolines and operating conditions. Suitable for all gasoline injection systems, both direct and manifold fuel injection systems and combined systems.

Application

To be added directly into the fuel tank. As a preventive measure, add during each inspection, after repairs on the fuel system and after each JetClean cleaning operation. The product mixes with fuel automatically. Contents of can are sufficient for max. 70 l of fuel.

Available pack sizes

500 ml Can sheet metal	2970 AR-DE-EL-FR-NL

Available pack sizes

500 ml Can sheet metal	2979 DA-EN-FI-NO-SV
500 ml Can sheet metal	5153 DE-EN-ES-IT-PT
500 ml Can sheet metal	20453 BG-DE-PL
500 ml Can sheet metal	20917 JP
500 ml Can sheet metal	21601 AUEN-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com