Product information

PI 50/07/03/2025

Motorbike 4T Synth 10W-50 Street Race



Description

Fully synthetic high-performance motor oil. Ensures maximum performance and protection of the engine under all operating conditions. Optimum lubrication, outstanding engine cleanliness, excellent friction values and minimum wear are just as much par for the course as gentle clutch engagement and disengagement and gear shifting. That makes a big difference to driving enjoyment! Tested on engines with catalytic converters. Tested on racing machines. exposed to normal to extreme operating conditions. For sporting applications. Suitable for engines with or without a wet clutch.

Properties

- excellent wear protection
- optimum stability to aging
- high shear stability
- tested for the use with catalytic converters
- especially suitable for wet clutches
- guarantees low oil consumption
- optimum lubrication under all operating conditions

Specifications

API SP • JASO MA2

Technical data

SAE class (engine oils)	10W-50 SAE J300
Density at 15 °C	0,850 g/cm³ DIN 51757
Viscosity at 40 °C	124,0 mm²/s ASTM D 7042-04
Viscosity at 100 °C	18,5 mm²/s ASTM D 7042-04
Viscosity index	165 DIN ISO 2909
Viscosity at -25 °C (CCS)	<= 7000 mPas ASTM D 5293
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	4,5 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,0 mg KOH/g DIN ISO 3771
Sulfate ash	0,8 g/100g DIN 51575
Color number (ASTM)	L 2,0 DIN 51578

Areas of application

Developed for air and water-cooled 4-stroke engines

Application

The operating instructions of the engine manufacturers must be followed.
Note: Optimum effectiveness only when the product is used unmixed.

Available pack sizes

1 l Canister plastic	1502 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
1 l Canister plastic	1751 JA
4 l Canister plastic	1686 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
20 l Canister plastic	1567 DE-EN
20 l Canister plastic	20852 JA
60 l Black plate barrel	1564 DE-EN
205 l Black plate barrel	1569 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com