Product information

PI 36/06/17/2025

Molygen New Generation 10W-30



Description

High performance low-friction motor oil for year-round use. The combination of unconventional base oils and advanced additive technology as well as the special Molygen additive ensures that the motor oil is of low viscosity with a high shear stability and reliably prevents the formation of deposits, significantly reduces frictional losses in the engine and provides the optimum protection from wear. This results in fuel savings and an extended service life for the engine.

Properties

- excellent wear resistance
- friction and wear reducing
- smooth engine running
- tested for turbochargers and catalytic converters
- outstanding engine cleanliness
- outstanding shear resistance
- excellent high and low temperature behavior
- outstanding lubrication reliability
- miscible with all commercially available motor oils
- optimum stability to aging

Specifications / Approvals

API SQ • ILSAC GF-7A

LIQUI MOLY recommends this product for vehicles or assemblies for which the following specifications or original spare part numbers are required:

Chrysler MS-6395 • Daihatsu • Fiat 9.55535-CR1 • Ford • GM • GM 6094 M • Honda • Hyundai • Isuzu • Kia • Mazda • Mitsubishi • Nissan • Subaru • Suzuki • Toyota

Technical data

SAE class (engine oils)	10W-30 SAE J300
Density at 15 °C	0,85 g/cm³ DIN 51757
Viscosity at 40 °C	66,9 mm²/s ASTM D 7042-04
Viscosity at 100 °C	11 mm²/s ASTM D 7042-04
Viscosity at -30 °C (MRV)	<= 60000 mPas ASTM D 4684
Viscosity at -25 °C (CCS)	>= 7000 mPas ASTM D 5293
Viscosity index	156 DIN ISO 2909
HTHS at 150°C	>= 2,9 mPas ASTM D 5481

Technical data

Pour point	-42 °C DIN ISO 3016
Evaporation loss (Noack)	8,2 % CEC-L-40-A-93
Flash point	238 °C DIN ISO 2592
Total base number	7,1 mg KOH/g DIN ISO 3771
Sulfate ash	< 0,8 g/100g DIN 51575
Color / appearance	green-brown, fluorescent

Areas of application

Ideal for modern Asian and American gasoline engines with multi-valve technology and turbocharging with and without charge air cooling. For the protection and value retention of the engine during long intervals between oil changes and where there are extreme demands on the engine.

Application

The operating instructions of the vehicle and engine manufacturers must be followed. Can be mixed with all commercially available motor oils. Optimum effectiveness is only possible when the product is used unmixed.

Available pack sizes

1 l Canister plastic	9975 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
4 l Canister plastic	20797 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH
5 l Canister plastic	9978 AR-BG-CS-DA-EL-EN-ES-FI-FR-HR-HU-ID-IT-KK-NL-NO-PL-PT-RO-RU-SK-SV-TR-UK-ZH

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com

Product information

PI 36/06/17/2025

Molygen New Generation 10W-30

Available pack sizes

205 l Black plate barrel	8422 DE-EN

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com