Product information
GUNTEC Gun Grease

PI 21/11/06/2025



Description
Strongly adherent synthetic special grease with ceramic solid lubricants. Ensures the safe functioning of all types of weapons due to its excellent lubricating effect. Due to their emergency running properties, the solid lubricants contained ensure the lowest friction coefficients and best possible wear protection even in critical lubrication situations. Offers the necessary corrosion protection for all metallic components even under extreme operating conditions.

Properties
- PTFE-free
- outstanding corrosion protection
- excellent wear resistance
- does not contain resins or acids
- extremely low friction
- waterproof
- high-strength adhesion
- very compatible with plastics
- wide operating temperature range
- long-term stability

Technical data

Odor	odourless
Form	paste with solids
Color / appearance	white
Water soluble	insoluble
Operating temperature range	-36 - +185 °C
Temperature range for solid lubricant contained	1100 °C

Areas of application
For lubrication of guns and weapon components of all kinds. Especially suitable for metal/plastic or metal/metal and plastic/plastic friction pairings in guns and precision mechanical components. Also for the lubrication of components in the low temperature range as well as components which are subject to a wide operating temperature range.

Application
Shake well before use. Carefully clean parts before greasing. Old grease residues can be easily removed with LIQUI MOLY Rapid Cleaner (part no. 3318). Apply a thin layer to the lubrication points after drying.

Available pack sizes

20 ml Tube plastic	24397 EN
50 ml Blister	24392 DE-EN

Available pack sizes

50 ml Tube plastic	24400 DA-EN-FI-NO-SV

Our information is based on thorough research and may be considered reliable, although not legally binding.

LIQUI MOLY GmbH
Jerg-Wieland-Str. 4
89081 Ulm-Lehr

Phone: +49 (0)731/1420-0
Fax: +49 (0)731/1420-82
e-mail: info@liqui-moly.de

Technical hotline: +49 (0)731/1420-871
www.liqui-moly.com